# A THERMOSTAT COMPANY DESIGNED FOR THE PROFESSIONAL TRADE



#### U High Quality

Pro1 thermostats are professional grade, built on proven performance and reliability. It's a difference you can see and feel.

#### One Size Thermostats

All Pro1 thermostats have the same size footprint, so you never have to worry about wall marks left by old models. You can also upgrade to new models including WIFI without rewiring using the interchangeable subbase system.

#### U Full Offering

We offer a full line of thermostats for nearly every application. Whether you need a basic 1 heat, 1 cool non-programmable or a 4 heat, 2 cool WIFI thermostat, Pro1 has you covered.

#### **U** Badge System

All Pro1 thermostats share a removable badge that can easily be replaced with a custom badge that has your contact information. This free service is a great way to generate future business for your company.



### EXCLUSIVELY FOR PROFESSIONALS





Google Play is a trademark of Google Inc., Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark

## THE ORIGINAL BRAND FOR PROFESSIONALS





	PRO.			l	C Commercial Time Periods (Occupied/Unoccupied) 7D 7 Day Programmable 5/1/1 5/1/1 Programmable NP Non-Programmable FC Fully Customizable in App	Stages of Heat	of Cool	Gas, Electric or Oil Heat Pump with	Auxiliary Heat Pump without Auxiliary	PTAC Mode	Battery Power	120 Line Voltage 24V Power (Hardwire)	Outdoor Temperature Sensor Compatible	Dual Fuel Compatible Display Size	Auto Changeover	Filter Change Reminder Room Temperature Calbration	Minimum Compressor Run Time	Compressor Short Cycle Delay	Adjustable Heat & Cool Temperature Swing	Cooling Fan Delay	Programmable Fan	Pre-Occupancy Fan Purge	IAQ Fan Mode Always on Display Light	Keypad Lockout Adjustable Setpoint	Humidity Control	Memory Type (Permanent)	Remote Sensor Capable	Millivolt	Warranty	Terminals
	Accessories			Pro1 Model #																										
Model Z2K955WDA	Description Two Zone Kit	Compatible With Zoning Models	_	T855i	7D 5/1/1 NP FC C	4*	2		•			•		• 8	•		•	•	•	•	•	•	• •			•			5 !	Rh, Rc, C, Y, Y2, W/E, W2, G, O, B
RZ251W	Secondary Zone Controller / Wireless	Z955W	×	T701i	FC	1		•	•			•		4		•		•	•				•	•		•				Rh, Rc, C, Y, W, G, O, B
	Remote Sensor Wireless Outdoor	T955WH Z955W	10	Z955W	7D 5/1/1 NP	3*	2		•		•	•	•	• 13		• •	•	•	•	•	•					• •		П	5 !	Rh, Rc, C, Y, Y2, W/E, W2, G, O, B
RZ250W	Sensor	T955WH	WIRELESS	T955WH	7D 5/1/1 NP C	3*		• •	•		•	•		• 13		• •	•	•	•	•	•	•	•		•	• •	. •			Rh, Rc, C, Y, Y2, W/E, W2, G, O, B, H, D
Z260W	Wireless Damper Module	Z955W		T631W-2	NP	2		•	•	•	•	•		2		•		•	•					•		•		_		R, C, Y, W, GH, GL, O/B
ZDA250W	Wireless Discharge Air Sensor	Z955W	EST	T955S	7D 5/1/1 NP C	3*	2				•	•	•	• 13	•		•	•	•	•	•	•						•	5 1	Rh, Rc, C, Y, Y2, W/E, W2, G, O, B, S1, S2
W150W	Wireless Repeater	Wireless Models		T955	7D 5/1/1 NP C	3*		• •	•		•	•		• 13		• •	•	•	•	•	•	•	• •	• •		• •	,	_		Rh, Rc, C, Y, Y2, W/E, W2, G, O, B
WW160W	Wireless Wire	24V	-	T905	7D 5/1/1 NP	1		•	•		•	•		13		• •	•	•	•		•			• •		• •	,	•	5 F	Rh, Rc, C, Y, W, G, O, B
R250S	Wired Outdoor Temperature Sensor	T755S T855SH		T855SH	7D 5/1/1 NP C	5*	3		•	•	•	•	•	• 8	•		•	•	•			•			•	•	•	•	5 R	Rh, Rc, C, Y, Y2, W/E, W2, G, B, O, S1, S2, H, D
	Wired Indoor Temperature Sensor	T955S T755S T855SH T955S	TTER	T855	7D 5/1/1 NP C	3*		•	•	•	•	•		• 8	•	• •	•	•	•	• •	•	•	• •	• •		•		•		Rh, Rc, C, Y, Y2, W/E, W2, G, O, B
R251S				T805	7D 5/1/1 NP	1	1	•	•		•	•		8	•	• •	•	•	•		•			• •		•		•	5 F	Rh, Rc, C, Y, W, G, O, B
T150	Stat Guard Cover	Any Thermostat		T771	NP	0/1	0/1	•			•	•		4		•		•	•					•		•		•	5 I	R, C, W/Y, G
T119	Universal Wall Plate	Any Thermostat		T755H	7D 5/1/1 NP	3*	2	•	•		•	•		• 6		• •	•	•	•	•	•			•	•	•		•	5 F	Rh, Rc, C, Y, Y2, W/E, W2, G, O, B, H, D
E219	Weather Resistant	Any		T755S	7D 5/1/1 NP	3*	2	•	•		•	•	•	• 6		• •	•	•	•	•	•			•		•	•	•	5 F	Rh, Rc, C, Y, Y2, W/E, W2, G, O, B, S1, S2
2217	Junction Box	Thermostat	۵	T755	7D 5/1/1 NP	3*	2	• •	•		•	•		• 6		• •	•	•	•	•	•			•		•	$\bot$	•	5 F	Rh, Rc, C, Y, Y2, W/E, W2, G, O, B
Mo	Model # Nomenclature		000	T725	7D 5/1/1 NP	2			•		•	•		• 4		• •		•	•					•		•		_	_	R, C, Y, W2, W/E, G, O, B
Prefix  The sympostot	PrefixT - ThermostatsDA - Discharge Air SensorR - Remote SensorZ - Zoning Capable			T721	NP				•		•	•		• 4		•		•	•					•		•	$\bot$			R, C, Y, W2, W/E, G, O, B
				T715	7D 5/1/1 NP			•	•		•	•		4		• •		•	•					•		•	4	_		Rh, Rc, C, Y, Y2, W, W2, G, O, B
First Number	First Number         6 - 600 Platform       8 - 800 Platform         7 - 700 Platform       9 - 900 Platform			T705	7D 5/1/1 NP			•	•		•	•		4		• •		•	•					•		•				Rh, Rc, C, Y, W, G, O, B
				T701	NP			•	•		•	•	$\blacksquare$	4		•		•	•					•		•				Rh, Rc, C, Y, W, G, O, B
Second Number	2 11-1	LDTAG		T631-2	NP	2		• •	•	•	•	•	$\sqcup$	2		•		•	•					•		•				R, C, Y, W, GH, GL, O/B
<b>1</b> - Multi Stage	<ul> <li>0 - Single Stage</li> <li>1 - Multi Stage Gas</li> <li>2 - Multi Stage Heat Pump</li> <li>Third Number</li> <li>1 - Non-Programmable</li> <li>5 - Universal Multi Stage</li> <li>7 - Heating or cooling</li> </ul>		)ER	T625-2	7D 5/1/1	2			•		•	•		• 2		•		•	•					•		•	4			R, C, Y, W2, E, G, O, B
9			BUILD	T621-2	NP	2		• •			•	•		• 2		•		•	•					•		•				R, C, Y, W2, E, G, O, B
1 - Non-Progra				T605-2	7D 5/1/1	1	-	•	•		•	•		2		•		•	•					•		•		_		Rh, Rc, C, Y, W, G, O, B
5 - Programmable  Suffix				T601-2	NP		•				7			2		•			_											Rh, Rc, C, Y, W, G, O, B
<b>W</b> - Wireless <b>H</b> - Humidity (	S - Wired	Capable Number	NICAL	T501M	NP	1		•	•																	4		_		Rh, Rc, Y, W, G, O, B
i - Internet Cap	oable <b>-2</b> - Series		CHA	T501ML4	NP	1	0					•																_	2 4	
<b>M</b> - Mechanica	al <b>L</b> - Line Vo	onage	Σ	T501ML2	NP		0					•														400		4	2 2	z wire

Stages \* = 2 Stages for conventional heat v. 1933

THE PUWER OF PARTNERSHIP www.proliaq.com 1-888-PRO1-IAQ (776-1427)