

EZ-Ject™ (Patented) Fluorescent Dye Injection System

The revolutionary way to add fluorescent dyes into air conditioning and refrigeration systems — without the use of additional refrigerant, manifold and additional hoses.

- ▶ No pouring and no refrigerant required for injection.
- ▶ One calibrated cartridge provides exact dosing for multiple systems. Easily overcomes system pressure.
- ▶ Inject dye with a turn of the handle.



AR-GLO 5E: Brighter Performance Dye

Works in all AC&R systems, overcomes system pressure up to:

450
PSI



Co-Solvent Free Dye



Multi-Dose Cartridge



S-M

Small-Medium
Sized AC&R Systems



EZ-Ject™ COMPLETE Fluorescent Leak Detection Kit

SPE-HVLEZE

- ▶ SPE-HVL-CS violet light LED leak detection lamp
- ▶ SPE-EZ5E (2) 0.5 oz (15 ml) universal/POE dye cartridges
- ▶ EZ-50 EZ-Ject™ dye injector assembly
- ▶ EZ-25 8 in (20 cm) EZ-Ject™ hose assembly with low-loss fitting & check valve
- ▶ 128186 R-410a adapter



Universal/POE Dye: NSF Certified to meet food-grade processing requirements for category codes HTX-2 and HX-2



EZ-Ject™ Fluorescent Dye Injection Kit

SPE-EZ100E-CS

- ▶ (2) SPE-EZ5E 0.5 oz (15 ml) universal/POE dye cartridges
- ▶ EZ-50 EZ-Ject™ dye injector assembly
- ▶ EZ-25 8 in (20 cm) EZ-Ject™ hose assembly with low-loss fitting & check valve
- ▶ 128186 R-410a adapter

Treats a TOTAL of up to:

- ▶ 4 gal (15.2 ml) of lubricant or
- ▶ 50 lbs (22.6 kg) of refrigerant or
- ▶ 24 tons (84.4 kW) of cooling



EZ-Ject™ Fluorescent Dye Cartridge

SPE-EZ5E-CS

- ▶ 0.5 oz (15 ml) universal/POE dye cartridge

Treats up to:

- ▶ 2 gal (76 ml) of lubricant or
- ▶ 25 lbs (11.3 kg) of refrigerant or
- ▶ 12 tons (42.2 kW) of cooling

