

ASMT402 | MAESTRO™

SMART THERMOSTAT

4000 W

MAESTRO™

DESIGNED FOR:



HARMONIZES WITH
MAESTRO



ORCHESTRATING COMFORT

Use the MAESTRO thermostat with the MAESTRO controller•thermostat to turn your house into a smart home in a snap! Indeed, the MAESTRO thermostat reveals its full potential when it's paired with the MAESTRO controller•thermostat. It can also be linked to an existing Zigbee network controlled by any Zigbee-compatible controller. Maestro is the smart home comfort solution!



**COMPATIBLE WITH MAESTRO
CONTROLLER OR ZIGBEE HUB**
CONTROL AT YOUR FINGERTIPS
WITH YOUR SMARTPHONE OR
MOBILE DEVICE



**RELATIVE ROOM
HUMIDITY DISPLAY**



ENERGY CONSUMPTION REPORTS*
FOR OPTIMAL ENERGY EFFICIENCY



ELECTRICITY SAVINGS
ENERGY SAVINGS UP TO 25%
DEPENDENT ON USE*

COMPATIBILITY

- MAESTRO controller•thermostat or Zigbee hub required

COLOR

- white

FINISH

- molded plastic

WATTAGE AND VOLTAGE

- 150 W to 2000 W @ 120 V
- 260 W to 3400 W @ 208 V
- 300 W to 4000 W @ 240 V

CONTROL

- two- or four-wire connection
- MAESTRO environment options include:
 - outdoor temperature or relative room humidity display
 - energy consumption reports

- lock screen capability
- screen backlighting
- radical temperature decrease detection (open-window feature)
- motion-activated screen
- Zigbee home automation environment compatibility

ACCURACY

- accurate ambient temperature control of ± 1 °F
- CSA C828-13
- temperature sensing with thermistor

TEMPERATURE RANGE

- 41 to 86 °F

WARRANTY

- three years

† with MAESTRO ecosystem

* study carried out by an independent university team

ACCESSORIES

PRODUCT	DESCRIPTION	PRICE
SMAMPLIZB	Zigbee signal amplifier	139.00
SMREPETZB	Zigbee signal repeater	94.00

COMPATIBLE WITH



FOR HOME AUTOMATED SYSTEM COMPATIBILITIES AND INSTRUCTIONS ON CONNECTING TO YOUR MAESTRO THERMOSTAT, VISIT WWW.STELPRO.COM/MAESTRO.

TECHNICAL SPECIFICATIONS

PRODUCT	WATTS		VOLTAGE	AMPERAGE	FREQUENCY	COLOR	PACKAGING	UNIT PRICE
CODE	MINIMUM	MAXIMUM	VOLTS	AMPERES	HZ			
ASMT402	150/260/300	2000/3400/4000	120/208/240	16.7	50/60	WHITE	BOX	144.50

Dimensions: 5 3/8 in. wide, 5 3/8 in. high and 1 1/4 in. deep

°STELPRO

°STELPRO reserves the right to modify descriptions, manufacturing specifications or prices without prior notice. No returns accepted on optional-color products. For all the latest models and prices, please refer to our website at www.stelpro.com.



FC_SMT402_US_290419