



Indoor Comfort Products Brought to You
by the Manufactured Home Experts!

M5SB 83% AFUE Downflow MH Oil Furnaces




Unique Manufactured Housing Design with a robust, 19 $\frac{3}{4}$ "W, fully-insulated cabinet to fit the standard MH footprint; the M5SB is our latest HUD-compliant, oil furnace.

AC-Ready Options include a factory-installed 20"H coil box, field-installed 20"H/26"H coil box, and PSC blower upgrades for up to 5-Tons nominal cooling. (See Split System sell sheets for coil fit and AHRI-rated matches.)

High-Performance Combustion System including a Beckett burner and drum heat exchanger, which contribute to the overall efficiency, reliability, and homeowner's peace of mind.

Numerous Application Accessories save the hassle of field-fabrication, sourcing and repeat supply-house trips; on new or replacement jobs.

Dependable Warranty and Support, handled directly by Style Crest's dedicated HVAC Team, offering the most competitive warranty coverage and service in the Manufactured Housing Industry.



M5SB 83% AFUE Downflow MH Oil Furnaces


SKU	Coil Box	AHRI Cert. #	Input	Heating Capacity	Ship L	Ship W	Ship H	Ship Wt.	Nozzle	AC (PSC) Blower	MOCP
M5SB-066A-AW	No, Optional ¹	201928967	66 MBH	56 MBH	26 1/2"	21 5/16"	58 1/8"	151#	.50 Gph, 80°A	3T, 1/4hp	15A
M5SB-086A-AW	No, Optional ¹	201928968	86 MBH	72 MBH	26 1/2"	21 5/16"	58 1/8"	158#	.65 Gph, 80°A	3T, 1/4hp	15A
M5SB-066A-BW	Yes, 20"H	201928967	66 MBH	56 MBH	26 1/2"	21 5/16"	78 1/8"	165#	.50 Gph, 80°A	3T, 1/4hp	15A
M5SB-086A-BW	Yes, 20"H	201928968	86 MBH	72 MBH	26 1/2"	21 5/16"	78 1/8"	173#	.65 Gph, 80°A	3T, 1/4hp	15A

1) If adding a central air split system, you must also order a separate field-installed coil box, listed in the Application Accessories table below.

Roof Jack Accessories

Roof Jack Length Range	Roof / Roof Jack Flashing Pitch		
	0"↑x12"→	2 1/2"↑x12"→	4"↑x12"→
	RJ SKU	RJ SKU	RJ SKU
15"-23"	903658		
21"-35"	903659	903662	
27"-47"	903660	903663	903678A
35"-63"		903664	903665A
51"-95"		920638	903666A

- "A" + "B" + "X" = Roof Jack Length.
- "X" is included only if a wedge is used, see table (below) for "X" Value.
- "A" = Roof Height - Ceiling Height.
- "B" = Ceiling Height - Furnace Height.
- Measure with respect to RJ center-line.
- The calculated Roof Jack Length must be within the "Range" (table-above).
- 0/12 Flashing flexes from 0/12 to 1/12.
- 2 1/2/12 Flashing flexes from 1/12 to 4/12.
- 4/12 Flashing flexes from 3/12 to 5/12.



Total Pitch with RJ Pitch		Roof Wedge			
0"↑x12"→	2 1/2"↑x12"→	SKU	Qty	Pitch	X-Value
2"↑x12"→	4 1/2"↑x12"→	903893	1 (4/Ctn)	2 1/2"↑x12"→	2 1/8"
2 1/2"↑x12"→	5"↑x12"→				2 1/2"
3"↑x12"→	5 1/2"↑x12"→	903894	1 (4/Ctn)	3"↑x12"→	2 7/8"
3 1/2"↑x12"→	6"↑x12"→				3 1/4"
4"↑x12"→	6 1/2"↑x12"→	903895	1 (2/Ctn)	4"↑x12"→	3 5/8"

Application Accessories

Item SKU	Item Description
911969A	Coil Box, 20"H, Field-Installed, Central Air
922594	Coil Box, 26"H, Field-Installed, Central Air
903890	5-Ton AC-Blower Upgrade Kit, 4-Speed
903413	4-Ton AC-Blower Upgrade Kit, 4-Speed
901083	Backflow Damper, 1-Blade, Empty Box
902095	Backflow Damper, 3-Blade, Low Profile
901935	Roof Jack Extension, 10"H, Internal
903107	Roof Jack Extension, 18"H, Internal
901937	Roof Jack Extension, 16"H, External

Item SKU	Item Description
901987A	Duct Connector, 11 1/4"x13 1/2"x7 7/8"H, EA (12/Ctn)
901988A	Duct Connector, 11 1/4"x13 1/2"x2"H, EA (12/Ctn)
901989A	Duct Connector, 11 1/4"x13 1/2"x4 1/4"H, EA (6/Ctn)
901990A	Duct Connector, 11 1/4"x13 1/2"x6 1/4"H, EA (6/Ctn)
901991A	Duct Connector, 11 1/4"x13 1/2"x8 1/4"H, EA (4/Ctn)
901992A	Duct Connector, 11 1/4"x13 1/2"x10 1/4"H, EA (3/Ctn)
901993A	Duct Connector, 11 1/4"x13 1/2"x12 1/4"H, EA (3/Ctn)
902521	Ceiling Ring-Halves, Adjustable, 2-Pieces
903656	Roof Jack, Crown-Only (Post-Transit)