### Honeywell Home HPSR10\*



### HYDRONIC PRO CONTROLLER

## Job Name Engineer Mechanical Contractor Contractor's P.O. No. Representative Notes

# Honeywell Home The state of th

### **APPLICATION**

Honeywell Home's Hydronic Switching Relays are the new standard for Hydronic controls, providing simplified setup and wiring for quick installation.

### **SUBMITTAL SHEET**

Model(s)			
HPSR101	Qty.	Notes	
HPSR103	Qty.	Notes	
HPSR104	Qty.	Notes	
HPSR106	Qty.	Notes	
Approval			
Service			
Tag No.		<u> </u>	

### **FEATURES**

- Familiar Setup
- Flexible mounting
- · Color coded wiring and terminals
- Simple layout cover
- · Hinged door
- Integrated and visible LED panel
- Works with power stealing stats without the need of an additional resistor
- Auto-resettable fuses as well as backup glass fuses for double protection
- · High output transformers for more power
- 5-year warranty

### **INCLUDED IN THE BOX**

- · Zoning Panel
- Mounting Hardware (3 Screws and 3 Wall Anchors)
- 2, 2-Amp Fuses
- Spare Status Label (French)
- Install Manuals (English & French)

### **SPECIFICATIONS**

Model	Zones	Transformers	Input Power	Maximum Combined	Pump Fuse	Priority Zone	Type 1 Enclosure		
				Load		Control	Width	Height	Depth
HPSR101	1	1	120/60/1 VAC	15 amps	6 Amp	No	5-1/8"	6-3/4"	2-3/8"
HPSR103	3	1	120/60/1 VAC	15 amps	6 Amp	Yes	11-3/4"	8-3/4"	2-1/8"
HPSR104	4	1	120/60/1 VAC	20 amps	6 Amp	Yes	11-3/4"	8-3/4"	2-1/8"
HPSR106	6	1	120/60/1 VAC	20 amps	6 Amp	Yes	11-3/4"	8-3/4"	2-1/8"

### Notes:

- All circulator relay connections, including ZC/ZR, are rated 1/3 hp (6FLA, 36LRA) at 120 VAC.
- End switch connections are rated 24 VAC, 1 amp.
- All thermostat connections supply a 24 VAC class 2 output.



Resideo Technologies, Inc. 1985 Douglas Drive North, Golden Valley, MN 55422 1-800-468-1502 33-00380-02 M.S. Rev. 01-21 | Printed in United States

33-00380-02