

FTMA4

Two Stage Fan Coil

2, 3, 4, and 5 Tons



Standard Features

- Two stage operation with dehumidification capability
- Aluminum Tube, Aluminum Fin Evaporator Coil
- Factory installed TXV w/mechanical fitting connection
- Multiposition installation – upflow or horizontal left standard, horizontal right with minor modification (field convertible to downflow with accessory kits)
- Modular cabinets for easier installation in space constrained areas
- 2023 design EHC electrical heaters will be compatible
- Field installed heater packages from 5 kW – 30 kW available separately

Limited Warranty*

- Five-year No Hassle Replacement™ limited warranty
- Five-year parts limited warranty
 - With timely registration, an additional five-year parts limited warranty

* For residential applications only.
See warranty certificate for complete details and restrictions, including warranty coverage for other applications.



ISO 9001
QMS-6A1 Global



Use of the AHRI Certified TM Mark indicates a manufacturer's participation in the program. For verification of certification for individual products, go to www.ahridirectory.org.

Unit Performance Data

Model Number	Size (tons)	Nominal Btu/hr	CFM (L/s) Range		Operating Dimensions height x width x depth in. (mm)	SINGLE CIRCUIT		Unit Ship Weight lbs. (kg)
			Low	High		MCA	MOCP	
FTMA4X24L0BA	2	24,000	400	1400	42-11/16 x 17-5/8 x 22-1/16 (1084 x 448 x 560)	5	15	TBD
FTMA4B36L0CA	3	36,000	400	1600	53-7/16 x 21-1/8 x 22-1/16 (1357 x 537 x 560)	5	15	TBD
FTMA4B48L0CA	4	48,000	400	1600	53-7/16 x 21-1/8 x 22-1/16 (1357 x 537 x 560)	7.1	15	TBD
FTMA4B60L0DA	5	60,000	600	2150	59-3/16 x 24-11/16 x 22-1/16 (1503 x 627 x 560)	7.1	15	TBD