

Easy to Use. Removes
scale, lime, rust and corrosion fast.

BLUE MONSTER®

Velocity Tankless Water-Heater Flush

Cleans and Restores Flow
and Efficiency to 100%!

Velocity™

Tankless Water-Heater Flush



**Use on
Commercial
& Residential
Tankless
Water Heaters**



Nonfood Compounds
A3

FEATURES / BENEFITS

- Restores circulation and pressure in under 20 minutes
- Dissolves lime, water scale and rust deposits
- Granules eliminate splashes and spills
- Easy to use – Mix BLUE MONSTER® Velocity™ with water and circulate through system for a complete flush
- Odorless
- For commercial and residential use

BLUE MONSTER® Velocity™ is a hard-hitting, fast-acting compound with the strength needed to remove scale, lime, rust, and other corrosive water-formed deposits inside on-demand water heaters. Velocity™ contains sulfamic acid, a highly-effective agent used to clean heat exchangers, boilers and condensers. Restore water flow and heating efficiency for like-new performance with Velocity™.

BLUE MONSTER® Velocity™ is compatible with copper, CPVC, PEX, and PERT piping systems. It's non-corrosive and safe for potable water systems. BLUE MONSTER® Velocity™ is also NSF Nonfood Compounds A3 listed.

For Material Safety Data Sheets, contact Mill-Rose or download directly from the Mill-Rose Clean-Fit website.

DIRECTIONS FOR USE

Continuous Recirculation Heat Exchanger Flush
See Tankless manufacturer's service and maintenance instructions for flushing the heat exchanger.

Velocity is designed for use with the following:

1. Water circulation pump.
2. Minimum 5 gallon bucket.
3. Appliance water hose(s) with GHT FIP connections.



MIXING INSTRUCTIONS

1. Pour Velocity and 2 gallons of water into a 5 gallon bucket.
2. Use a stirring device to mix contents thoroughly.

RECIRCULATION INSTRUCTIONS

1. Follow manufacturer's instructions for connecting pump, hoses, tankless unit and bucket containing the cleaning solution.
2. Recirculate Velocity cleaning solution continuously for 20 minutes.
3. After cleaning dispose of Velocity cleaning solution in accordance with local regulations.

INSTRUCTIONS - RINSE CLEANING SOLUTION

1. Follow the manufacturer's instructions for removal of the cleaning solution from the unit.
2. Potable water rinse is required after use of this product for a minimum of 5 minutes.

UPON COMPLETION OF THE FLUSH

AND REMOVAL OF THE VELOCITY CLEANING SOLUTION

1. See manufacturer's service recommendations prior to restoring power, water, and fuel supply.

Cat #	Size	Case Pack	Weight
76052	1.2 net lbs.	12	15 lbs. (6.80 kg)



MILL-ROSE
Clean-Fit Products

7310 Corporate Blvd., Mentor, OH 44060

Orders 800.321.3598 or fax 440.255.1072 | BlueMonsterProducts.com | info@CleanFit.com