

Part No.	Name/ Specification	Description	Image
10-01-010	3" Ferrule PC/ABS UL94 V-0	3" ferrule fitting threads into the end of a duct, using a patent-pending design to ensure a near air-tight seal to the duct. Complies with Standard UL2043 and is identified as Classified with the ETL listed mark, control number 5016806. Complies with Standard UL181C and is identified as Certified with the UL listing mark, file number MH64419	
20-01-010	4" Ferrule PC/ABS UL94 V-0	4" ferrule fitting threads into the end of a duct, using a patent-pending design to ensure a near air-tight seal to the duct. Complies with Standard UL2043 and is identified as Classified with the ETL listed mark, control number 5016806.	
10-01-020	Elbow Extension PC/ABS UL94 V-0	45-degree fitting that is doubled up to form a 90-degree elbow where required. Used for tight radius duct transitions to ensure optimum airflow. UL 181C and UL2043 certified as part of a connector assembly. Complies with Standard UL2043 and is identified as Classified with the ETL listed mark, control number 5016806. Complies with Standard UL181C and is identified as Certified with the UL listing mark, file number MH64419	
10-01-030	Coupler PC/ABS UL94 V-0	Fitting used to connect two ducts together. Used to extend the length of a duct run. UL 181C and UL2043 certified as part of a connector assembly. Complies with Standard UL2043 and is identified as Classified with the ETL listed mark, control number 5016806. Complies with Standard UL181C and is identified as Certified with the UL listing mark, file number MH64419	