Rheia Product Specifications Sheet

Floor Boot 4x10 Assembly

Assembly Part # 10-01-280

For new constrution floor installations only.

Attaches directly to the floor surface. Includes an adjustable damper blade. Must be used with Rheia-approved Floor 4x10 Diffusers that are not equipped without a balancing damper.

SPECIFICATIONS

Intended Use

For installation into open web truss or I-joist floor systems. Floor boots complement the Rheia design providing a solution in applications where the Rheia supply duct cannot be run to a high-sidewall or pass-through boot.

Material

Floor Boot: Flame-retardant Polycarbonate /ABS blend. Damper Blade: Flame-retardant Polycarbonate /ABS blend. 100% recyclable.

Installation

Follow guidelines for floor deck maximum and minimum cut out sizes.

Fasten the boot to the floor decking with a minimum of four pan head wood screws with a minimum length of 3/4".

Listings

Manufactured with UL94 V-0 rated engineering thermoplastic.

Warranty


2-year limited warranty.

For additional warranty information please contact Rheia.


DIMENSIONS


Cut Out Guidelines

Floor cut out maximum: 45/8" x 105/8" +/-1/8" Floor cut out minimum: 43/8" x 103/8" +/-1/8" Minimum depth of deck surface to base of I-joist, truss, or dimensional joist: 10".









Only use the following approved floor registers or grilles with the Floor Boot 4x10 Assembly #10-01-280.

Failure to do so will affect the system's airflow performance.

Part #00-04-300. Color: White RAL9016 Part #00-04-300. Color: Beige Pantone 7531C Part #00-04-300. Color: Grey: Pantone Cool Gray 6C

