

Part No.	Name/ Flammability Rating	Description	Image
00-00-240	Hanger Bar Assembly 23 ga. galvanized sheet metal	Used for all boot installations where required. The hanger bar assembly allows installation within wall cavities, ceiling cavities, and bulkheads with spacing between 12" and 24".	
3" dia. 10-00-190 4" dia. 20-00-190	Uninsulated Duct UL 181 certified Class I Air duct	3" or 4" diameter uninsulated flexible duct available in 50' lengths.	
3" dia. 10-00-220 4" dia. 20-00-220	Insulated Duct UL 181 Listed Class I Air ducts	3" or 4" diameter r-8 insulated flexible duct available in 25' lengths.	
10-04-260	Ceiling Diffuser Small Assembly ABS UV stabilized UL94 HB	Two-part diffuser. Distributes air 360 degrees across a ceiling. Air throw pattern is designed specifically for heating dominated markets. Compatible with 5/8" or 1/2" thick drywall.	
10-01-280	Floor Boot 4x10 Assembly PC/ABS UL94 V-0	For floor installations. Attaches directly to the floor surface. Includes an adjustable damper blade. Must be used with the Rheia Metal Floor Diffuser 4x10 part # 00-04-300.	
00-04-300 00-05-300 00-06-300	Metal Floor Diffuser White: 00-04-300 Color Code: RAL 9016 Beige: 00-05-300 PANTONE 7531C Grey: 00-06-300 PANTONE COOL GREY 6C	One-piece drop-in assembly. Do not substitute with diffusers with a built-in adjustable damper.	