



Hydro Plus

*Next Generation
Well Tanks*





Features

- Seamless NSF 61 certified low permeability butyl diaphragm never creases and channels water directly to outlet, thus eliminating bacterial growth pockets
- MIG welding eliminates interior rough spots and sharp edges
- Low profile tank design reduces diaphragm motion to increase cycle life
- All diaphragms made by Zilmet specifically for each tank's dimensions
- Powdercoated exterior for a longer lasting, more durable finish

Specifications

- Working Pressure: 150 psi
- Max Temperature: 210° F
- Factory Precharge: 38 psi
- Warranty: 5 years



Well Tank Sizing Chart ZHP/BC

Pump GPM	30/50 psi		40/60 psi		50/70 psi	
	1 min	2 min	1 min	2 min	1 min	2 min
5	ZHP202	ZHP203	ZHP202	ZHP204 / 34	ZHP202	ZHP204
7	ZHP202	ZHP250	ZHP203	ZHP250	ZHP203	ZHP251
10	ZHP203	ZHP251	ZHP204	ZHP302	ZHP204 / 34	ZHP302
12	ZHP204 / 34	ZHP302	ZHP204 / 34	ZHP350	ZHP250	ZHP351
15	ZHP250	ZHP350	ZHP250	ZHP351	ZHP251	ZHP351
18	ZHP250	ZHP351	ZHP251	ZHP400	ZHP302	ZHP251 (2)
20	ZHP251	ZHP351	ZHP302	ZHP302 (2)	ZHP302	ZHP302 (2)
25	ZHP302	ZHP302 (2)	ZHP350	ZHP350 (2)	ZHP350	ZHP350 (2)
30	ZHP350	ZHP350 (2)	ZHP350	ZHP350 (2)	ZHP351	ZHP302 (3)
35	ZHP351	ZHP351 (2)	ZHP351	ZHP351 (2)	ZHP302 (2)	ZHP350 (3)
40	ZHP351	ZHP351 (2)	ZHP302 (2)	ZHP350 (3)	ZHP350 (2)	ZHP351 (3)

Recommended minimum pump runtime: Up to ¾hp = 1 minute Over ¾hp = 2 minutes

Stainless Steel In Line Models

For other Stainless Steel models available, please see catalog

Item	Capacity	Diameter	Height	Max Pressure	Precharge	Connection Size
	gallons	inches	inches	psi	psi	NPT
ZS8	2.1	7.8	10.8	150	36	¾"
ZS12	3.2	10.6	10.8	150	36	¾"
ZS18	4.8	10.6	14.2	150	36	¾"




Easy Installation in the Toughest Applications


- **Industry's Thickest Diaphragm**, molded with integral flow channels to turbulate water and avoid sticking
- **Powdercoat Plus Exterior Barrier** lasts up to 5 times longer than competitive finishes in exposure tests
- **All Models Suitable for Underground** burial in any position
- **Available in Next-Generation Side-Connection** or traditional bottom inlet for any installation
- **Industry's Largest Tank Producer**, with the widest range of well tank sizes and configurations
- **Smart, Pro-Focused Features** and the fastest-growing line of unique accessories and conditioning solutions



*Fresh water flow
flushes sediment*



*Standoff bumps
prevent sticking*




*Powdercoat in blue
or tan color*



*Accessories to create
a better system*

Stronger Where it Matters Most


- **Deep-Drawn Steel** with 150 psi rating on all models
- **Optimized Geometry** creates higher capacity and larger drawdowns with less diaphragm motion
- **Positive-Response Diaphragm Seal** works with internal forces, getting even stronger as pressure increases
- **Welded, 100% Stainless Steel Connection** for strength; no threaded carbon steel nipple or stainless waterway sleeve; elbow is welded directly to tank causing zero flexing
- **Rigid Composite Base**, withstands heavy loads and wet environments, with positive alignment for easy connection



*Optimized for
capacity & lifespan*



*Polymer tank base
aligns every time*



*Exterior groove
diaphragm seal*



*Side connection offers
simplicity and strength*

Bottom Connection Technical and Dimensional Data

<i>Item</i>	<i>Capacity</i>	<i>Diameter</i>	<i>Height</i>	<i>Base Diameter</i>	<i>Connection Height</i>	<i>Connection Size</i>	<i>System Drawdown</i>	
	<i>gallons</i>	<i>inches (D)</i>	<i>inches (H)</i>	<i>inches (B)</i>	<i>inches (E)</i>	<i>NPT (C)</i>	<i>30-50 psi</i>	<i>40-60 psi</i>
ZHP202BC	21.1	17.7	26.9	16.8	1.6	1"	7.2	6.2
ZHP202BVBC	21.1	17.7	27.9	16.8	1.6	1"	7.2	6.2
ZHP203BC	27.7	17.7	29.2	16.8	1.6	1 ¼"	9.5	8.2
ZHP34BC	34.1	19.7	33.9	16.8	1.6	1 ¼"	11.6	10.1
ZHP204BC	39.6	19.7	38.3	16.8	1.6	1 ¼"	13.5	11.7
ZHP250BC	54.7	19.7	49.7	16.8	1.6	1 ¼"	18.6	16.1
ZHP302BC	79.3	24.8	46.9	21.8	2.1	1 ¼"	27.0	23.4
ZHP351BC	119.0	24.8	65.9	21.8	2.1	1 ¼"	40.6	35.1

Side Connection Technical and Dimensional Data

<i>Type</i>	<i>Item</i>	<i>Capacity</i>	<i>Diameter</i>	<i>Height</i>	<i>Connection Height</i>	<i>Connection Size</i>	<i>System Drawdown</i>	
		<i>gallons</i>	<i>inches (D)</i>	<i>inches (H)</i>	<i>inches (E)</i>	<i>NPT (C)</i>	<i>30-50 psi</i>	<i>40-60 psi</i>
Stand Model	ZHP200F	13.2	15.0	19.9	6.0	1"	4.5	3.9
Stand Model	ZHP202	21.1	17.7	23.9	5.9	1"	7.2	6.2
Stand Model with Pump Bracket	ZHP202BV	21.1	17.7	24.4	5.9	1"	7.2	6.2
Stand Model	ZHP203	27.7	19.7	26.2	6.5	1 ¼"	9.5	8.2
Stand Model	ZHP204	39.6	19.7	35.3	8.5	1 ¼"	13.5	11.7
Stand Model	ZHP250	52.8	23.6	32.0	8.9	1 ¼"	18.0	15.6
Stand Model	ZHP251	66.0	24.8	37.7	9.6	1 ¼"	22.5	19.5
Stand Model	ZHP302	79.3	24.8	43.5	9.6	1 ¼"	27.0	23.4
Stand Model	ZHP350	105.7	24.8	57.1	9.6	1 ¼"	36.0	31.2
Stand Model	ZHP351	119.0	29.5	42.3	11.4	1 ¼"	40.6	35.1
Stand Model	ZHP400	132.1	29.5	52.8	11.4	1 ¼"	45.0	39.0
Stand Model	ZHP451	158.5	29.5	57.5	11.4	1 ¼"	54.0	46.8

Inline / Horizontal Technical and Dimensional Data

<i>Type</i>	<i>Item</i>	<i>Capacity</i>	<i>Diameter</i>	<i>Height</i>	<i>Connection Size</i>	<i>System Drawdown</i>	
		<i>gallons</i>	<i>inches (D)</i>	<i>inches (H)</i>	<i>NPT (C)</i>	<i>30-50 psi</i>	<i>40-60 psi</i>
Inline	ZEP5	2.1	7.9	11.0	¾"	0.7	0.6
Inline	ZEP12	4.8	10.6	13.7	¾"	1.6	1.4
Inline	ZEP18	6.3	11.8	15.4	¾"	2.2	1.9
Horizontal Model with Pump Bracket	ZHP24BH	6.3	11.8	13.5	1"	2.2	1.9
Inline	ZEP104IL	9.2	15.0	14.6	1"	3.1	2.7
Inline	ZEP200IL	13.2	15.0	19.6	1"	4.5	3.9
Horizontal Model with Pump Bracket	ZHP200BH	13.2	15.0	17.2	1"	4.5	3.9
Horizontal Model with Pump Bracket	ZHP202BV	21.1	17.7	19.1	1"	7.2	6.2
Horizontal Spacemaker	ZHP202SM	21.1	17.7	18.1	1"	7.2	6.2

Precharge: 38 psi

